


Industrial Computer



Gasmeter Industrial Computer

Gasmeter industrial computer is required to operate the analyser, to control the sampling system, translate measured and analysed concentrations and alarms to higher level automation and control systems.

In essence, the Gasmeter software (Calcmeter) can be operated in any Windows computer. However, many typical continuous monitoring applications require analogue inputs and outputs, relay contacts, status input and output values, all of which can optionally be provided by adding desired expansion cards to the Gasmeter industrial computer.

The standard computer configuration provides analyser control via a serial port, watchdog support and remote control for service and troubleshooting purposes. Additional features including sampling system control, current and alarm outputs and multipoint sampling can be realized by adding suitable expansion cards to the computer.

Standard configuration

Normal configuration:	Intel® Core™ i3-330E 2.13 GHz processor, 4 GB DDR3-SDRAM memory, 2 x 3.5" SATA HDD, RAID 1, Back-up hard disk (empty) and docking station, DVD-RW drive, network card (2 pcs)
Operating system:	Windows 7 (32-bit) (English)
Software included:	Calcmeter STD for Windows
Watchdog support:	Included
Mouse:	Optional
Keyboard:	Optional

Optional input / output expansion cards**AdLink PCI cards:**

- Analogue output 8 x 4-20 mA / card
- Digital input / output 16 x input / 16 x output / card
- Relay output 8 / card
- Analogue input 8 x 0-10 V / card (max. 8 cards)

Optional input / output expansion modules

Built in weather proof casing or on DIN rail.

Enclosure: IP66

Beckhoff:

- Digital output 8 x 0.5 A / module
- Digital input 8 / module
- Analogue output 8 x 4-20 mA / module
- Analogue input 4 x 4-20 mA / module,
4 x 0-10 V / module
(max. 255 modules)

FieldBus: ModBus, ModBus TCP/IP,
Profibus, ASCII, DDE link. RS232
or RS422/485

Electrical connections

- Networking:** 2 x LAN 10/100/1000 Mbit/s
Ethernet interface (RJ45, team
capability)
- USB connections:** 4 x USB 2.0 at the rear, 2 x USB
2.0 at the front (one of which can
be used when the front hatch is
closed)
- Serial/parallel ports:** COM1 (RS-232), COM2 (RS-232),
LPT1
- Audio:** Line out, microphone in
- Mouse:** PS/2
- Keyboard:** PS/2
- Display:** DVI-I

EMI protection / electrical safety

CE label: According to EMI guideline
89/336/EC

Enclosure

- Dimensions:** 19" rack, height 4 U
431 × 487 × 176 mm (W×D×H)
- Weight:** 16.7 kg

Gasmeter Technologies Oy shall not be liable for technical or editorial errors or omissions contained herein. The information in this document is provided "as is" without warranty of any kind and is subject to change without notice. Should you find any errors, we would appreciate if you notified us.